

ELECTROSTATICS

Coulomb force between two point charges

$$\vec{F} = \frac{1}{4\pi\epsilon_0\epsilon_r} \frac{q_1q_2}{|\vec{r}|^3} \vec{r} = \frac{1}{4\pi\epsilon_0\epsilon_r} \frac{q_1q_2}{|\vec{r}|^2} \hat{r}$$

- The electric field intensity at any point is the force experienced by unit positive charge, given by $\vec{E} = \frac{\vec{F}}{q_0}$
- Electric force on a charge 'q' at the position of electric field intensity \vec{E} produced by some source charges is $\vec{F} = q\vec{E}$
- Electric Potential

If $(W_{\infty P})_{\text{ext}}$ is the work required in moving a point charge q from infinity to a point P, the electric potential of the point P is

$$V_p = \frac{(W_{\infty p})_{\text{ext}}}{q} \Big]_{\text{acc}=0}$$

- **Potential Difference between two points A and B is**

$$V_A - V_B$$

- **Formulae of \vec{E} and potential V**

(i) Point charge $E = \frac{Kq}{|\vec{r}|^2} \cdot \hat{r} = \frac{Kq}{r^3} \vec{r}$, $V = \frac{Kq}{r}$

(ii) Infinitely long line charge $\frac{\lambda}{2\pi\epsilon_0 r} \hat{r} = \frac{2K\lambda \hat{r}}{r}$
 $V = \text{not defined}$, $v_B - v_A = -2K\lambda \ln(r_B / r_A)$

(iii) Infinite nonconducting thin sheet $\frac{\sigma}{2\epsilon_0} \hat{n}$,
 $V = \text{not defined}$, $v_B - v_A = -\frac{\sigma}{2\epsilon_0} (r_B - r_A)$

- (iv) Uniformly charged ring

$$E_{\text{axis}} = \frac{KQx}{(R^2 + x^2)^{3/2}}, \quad E_{\text{centre}} = 0$$

$$V_{\text{axis}} = \frac{KQ}{\sqrt{R^2 + x^2}}, \quad V_{\text{centre}} = \frac{KQ}{R}$$

x is the distance from centre along axis.

(v) Infinitely large charged conducting sheet $\frac{\sigma}{\epsilon_0} \hat{n}$

$$V = \text{not defined}$$
, $v_B - v_A = -\frac{\sigma}{\epsilon_0} (r_B - r_A)$

- (vi) Uniformly charged hollow conducting/ nonconducting /solid conducting sphere

(a) for $\vec{E} = \frac{kQ}{|\vec{r}|^2} \hat{r}$, $r \geq R$, $V = \frac{KQ}{r}$

(b) $\vec{E} = 0$ for $r < R$, $V = \frac{KQ}{R}$

(vii) Uniformly charged solid nonconducting sphere (insulating material)

(a) $\vec{E} = \frac{kQ}{|\vec{r}|^2} \hat{r}$ for $r \geq R$, $V = \frac{KQ}{r}$

(b) $\vec{E} = \frac{KQ\vec{r}}{R^3} = \frac{\rho\vec{r}}{3\epsilon_0}$ for $r \leq R$, $V = \frac{\rho}{6\epsilon_0} (3R^2 - r^2)$

(viii) thin uniformly charged disc (surface charge density is σ)

$$E_{\text{axis}} = \frac{\sigma}{2\epsilon_0} \left[1 - \frac{x}{\sqrt{R^2 + x^2}} \right] \quad V_{\text{axis}} = \frac{\sigma}{2\epsilon_0} \left[\sqrt{R^2 + x^2} - x \right]$$

- **Work done by external agent in taking a charge q from A to B is**
 $(W_{\text{ext}})_{AB} = q(V_B - V_A)$ or $(W_{\text{el}})_{AB} = q(V_A - V_B)$.

- **The electrostatic potential energy of a point charge**
 $U = qV$

- **U = PE of the system =**

$$\frac{U_1 + U_2 + \dots}{2} = (U_{12} + U_{13} + \dots + U_{1n}) + (U_{23} + U_{24} + \dots + U_{2n}) \\ + (U_{34} + U_{35} + \dots + U_{3n}) \dots$$

- **Energy Density =** $\frac{1}{2} \epsilon E^2$

- **Self Energy of a uniformly charged shell =** $U_{\text{self}} = \frac{KQ^2}{2R}$

- **Self Energy of a uniformly charged solid non-conducting sphere**

$$= U_{\text{self}} = \frac{3KQ^2}{5R}$$

- **Electric Field Intensity Due to Dipole**

(i) on the axis $\vec{E} = \frac{2K\vec{P}}{r^3}$

(ii) on the equatorial position : $\vec{E} = -\frac{K\vec{P}}{r^3}$

(iii) Total electric field at general point O (r, θ) is $E_{\text{res}} = \frac{KP}{r^3} \sqrt{1 + 3\cos^2 \theta}$

- **Potential Energy of an Electric Dipole in External Electric Field:**

$$U = - \vec{p} \cdot \vec{E}$$

- **Electric Dipole in Uniform Electric Field :**

$$\text{torque } \vec{\tau} = \vec{p} \times \vec{E}; \quad \vec{F} = 0$$

- **Electric Dipole in Nonuniform Electric Field:**

$$\text{torque } \vec{\tau} = \vec{p} \times \vec{E}; \quad U = - \vec{p} \cdot \vec{E}, \quad \text{Net force } |F| = \left| p \frac{\partial E}{\partial r} \right|$$

- **Electric Potential Due to Dipole at General Point (r, θ) :**

$$V = \frac{P \cos \theta}{4\pi\epsilon_0 r^2} = \frac{\vec{p} \cdot \vec{r}}{4\pi\epsilon_0 r^3}$$

- **The electric flux over the whole area is given by**

$$\phi_E = \int_S \vec{E} \cdot d\vec{S} = \int_S E_n dS$$

- **Flux using Gauss's law, Flux through a closed surface**

$$\phi_E = \oint \vec{E} \cdot d\vec{S} = \frac{q_{in}}{\epsilon_0}$$

- **Electric field intensity near the conducting surface**

$$= \frac{\sigma}{\epsilon_0} \hat{n}$$

- **Electric pressure :** Electric pressure at the surface of a conductor is given by formula

$$P = \frac{\sigma^2}{2\epsilon_0} \quad \text{where } \sigma \text{ is the local surface charge density.}$$

- **Potential difference between points A and B**

$$V_B - V_A = - \int_A^B \vec{E} \cdot d\vec{r}$$

$$\begin{aligned} \vec{E} &= - \left[\hat{i} \frac{\partial}{\partial x} V + \hat{j} \frac{\partial}{\partial y} V + \hat{k} \frac{\partial}{\partial z} V \right] = - \left[\hat{i} \frac{\partial}{\partial x} + \hat{j} \frac{\partial}{\partial y} + \hat{k} \frac{\partial}{\partial z} \right] V \\ &= - \nabla V = -\text{grad } V \end{aligned}$$